



SECTION I: TOOL STRING

Type 'A' Stem (Weight Bar): **3/8" – 2 1/2"**

Rebco Type 'A' Solid Bar Stems are with Threaded Connections – (1 1/4" - 2 1/2" Sucker Rod Type) 3/8" and 1/2" Diameter Stem is used for Velocity String Type completions

Note: All **Rebco** Tools have machined Flats for safer use.

TECHNICAL DATA				
ASSEMBLY PART NUMBER	NOMINAL SIZE (OD)	ENGINEERING DATA		
		LENGTH	THREAD CONNECTIONS	FISHING NECK
101000372	3/8"	24"	1/4" - 20 UNC	None
101000373		36"		
101000375		60"		
101000502	1/2"	24"	3/8" - 16 UNC	None
101000503		36"		
101000505		60"		
101000752	3/4"	24"	1/2" - 13 UNC	.687"
101000753		36"		
101000755		60"		
101001002	1"	24"	5/8" - 11 UNC	.750"
101001003		36"		
101001005		60"		
101001252	1 1/4"	24"	15/16" - 10 UNS	1.187"
101001253		36"		
101001255		60"		
101001502	1 1/2"	24"	1 1/16" - 10 UNS	1.375"
101001503		36"		
101001505		60"		
101001752	1 3/4"	24"	1 1/16" - 10 UNS	1.750"
101001753		36"		
101001755		60"		
101001872	1 7/8"	24"	1 1/16" - 10 UNS	1.750"
101001873		36"		
101001875		60"		
101002122	2 1/8"	24"	1 1/16" - 10 UNS	2.313"
101002123		36"		
101002125		60"		
101002502	2 1/2"	24"	1 9/16" - 10 UNS	2.313"
101002503		36"		
101002505		60"		
101002512		24"		
101002513		36"		
101002515		60"		

Alloy material is used to manufacture **Rebco** Stems; for severe conditions more suitable materials are available.

