



SECTION XIII: LANDING NIPPLES

TYPE 'BF' LANDING NIPPLE: Part No. 110125

Rebco Type 'BF' Landing Nipple is a Top No-Go or Selective Nipple.
The profile machined in the Nipple accepts Selective or Top No-Go Locks.

AVAILABILITY CHART:

TECHNICAL DATA						
Tubing OD		NIPPLE				
		Seal Bore		Size	Min OD	
Inches	mm	Inches	mm		Inches	mm
1.660	42.16	1.187	30.15	1.18	1.875	47.63
		1.250	31.75	1.25		
1.900	48.26	1.437	36.50	1.43	2.109	53.57
		1.500	38.10	1.50		
2 1/16	52.37	1.562	39.67	1.56	2.250	57.15
		1.625	41.28	1.62		
2 3/8	60.33	1.781	45.24	1.78	2.560	65.02
		1.812	46.02	1.81		
		1.875	47.63	1.87		
2 7/8	73.02	2.062	52.37	2.06	3.109	78.97
		2.250	57.15	2.25		
		2.312	58.72	2.31		
3 1/2	88.9	2.562	65.07	2.56	3.687	93.65
		2.750	69.85	2.75		
		2.812	71.42	2.81		
4	101.60	3.125	79.38	3.12	Coupling OD	
		3.250	82.55	3.25		
		3.312	84.12	3.31		
4 1/2	114.30	3.688	93.68	3.68		
		3.750	95.25	3.75		
		3.812	96.82	3.81		
5	127.0	4.000	101.60	4.00		
		4.125	104.78	4.12		
		4.312	109.52	4.31		
5 1/2	139.70	4.562	115.87	4.56		
		4.750	120.65	4.75		
6 5/8	168.28	5.250	133.35	5.25		
		5.500	139.70	5.50		
7	177.80	5.750	146.05	5.75		
		5.953	151.21	5.95		
7 5/8	193.68	6.125	155.58	6.12		
		6.375	161.92	6.37		



Type 'BF'

Min OD – Machined to the Tubing Joint OD or Coupling OD