

SECTION XIV: LOCK MANDRELS

Type 'ROTD' Collar Lock Mandrel Sub-Assembly: 2 3/8" - 3 1/2"

Rebco Type 'ROTD' Collar Lock Mandrel Sub-Assembly is designed to be set in API Tubing Collars. The Tubing is sealed off by adding the Type 'ROTD' Element Assembly, and variety of Sub-Assemblies to suit application; capable to hold pressure differentials in both directions.

TECHNICAL DATA						
NOMINAL SIZE		2″	2 1/2"	3″		
SUB-ASSEMBLY NUMBER		10032020030	10032025030	10032030030		
ENGINEERING DATA:						
MAXIMUM OD	BODY	1.84"	2.28"	2.84"		
	DOGS EXPANDED	2.11"	2.55"	3.11"		
MINIMUM ID		.94"	1.38″	1.75"		
FISHING NECK SIZE		1.38″	1.81″	2.31"		
BOTTOM THREAD - BOX		1 5/16" - 18	1 21/32" - 14	2 1/8" - 12		
LENGTH		13.50"	13.50"	13.88″		
MATERIAL		Norm Alloy	Norm Alloy	Norm Alloy		
RUNNING TOOL - 'ROTDO'		4103202000	4103202500	4103203000		
PULLING TOOL - 'ROTGSL'		4005140817800	4005140821800	4005140827500		



Product Code: 10

Product Code: 310

Rebco Type 'ROTD' Element Assembly (DET 8) is available as a Redress Kit.

TECHNICAL DATA					
NOMINAL SIZE	2"	2 1/2"	3"		
ELEMENT ASSEMBLY NUMBER	310032048	310032053	310032057		
ENGINEERING DATA:					
OD - ELEMENT EXPANDED	2.125"	2.625"	3.203"		
MINIMUM ID	.94"	1.38″	1.75"		
THREAD CONNECTIONS	1 5/16" - 18	1 21/32" - 14	2 1/8" - 12		
LENGTH	5.06"	5.06"	5.06"		
MATERIAL	Norm Alloy	Norm Alloy	Norm Alloy		



Page XIV-1

Rebco Oil Tools, Inc. Calgary, Alberta, Canada