



SECTION II: SERVICE TOOLS

Type 'A' Impression Block: 1" - 7"

The **Rebco** Type 'A' Impression Block is engineered to capture impressions of objects located within the tubing string.

A molded lead insert, secured by pins through the tool body, provides a smooth surface that records the shape and orientation of the obstruction. This allows operators to assess the fish's profile and position accurately before initiating retrieval operations.

Impression Blocks can be manufactured in custom sizes within the nominal outside diameter (OD) range. For available specifications, refer to Table 1 below.

Product Code: 108

Table 1: (PART NO. 10800_)

TECHNICAL DATA				
OD RANGE		THREAD	FISHING NECK	LENGTH
MIN	MAX			
.750	1.032	1/2" – 13	0.688	6.03
			0.750	
1.062	1.281	5/8" – 11	1.000	
1.296	1.468		1.187	6.56
1.500	1.730	15/16" – 10	1.375	
1.750	2.140		1.750	
2.156	2.375		2.313	
2.406	2.750	1 1/16" – 10	3.125	8.00
2.760	2.906			
2.937	3.468			
3.484	4.328			
4.375	5.906			
5.937	6.687			
Large Sizes		Custom order only: – Threads, FN and Length		



NOTES: How to Order

1. Part Number is 10800x.xxx – 0 for less than 1.00"
2. All Impression Blocks are Part Numbered by 'OD' dimension to 3 decimal places +/- .002"

Metric Dimensions are to be marked to 3 decimal places Part Number is 10801xxxx

1 inch = 2.540 cm

NOTE: **Rebco** can supply **Accessories** for re-pouring the Impression Blocks.




SECTION II: SERVICE TOOLS

Type 'A' Impression Block: **Accessory**

Accessory	Part No.
Lead Filler (Block)	108081
Lead Filler (Block)	108082

Reference:

Melting Point of Lead (Pb) is 327.5o C (621.5o F)



Pouring Ladle



Lead Filler (Block)