



SECTION V: SHIFTING TOOLS

Type 'ROTBP' Selective Positioning Tool Assembly: 2" – 4 1/2"

Rebco Type 'ROTBP' Selective Positioning Tool is designed to select and downshift only, several types of Sliding Sleeves. The tool is made selective by the feature of the lower section.

Type 'ROTBP' Selective Positioning Tool has a trip design that holds the shifting keys retracted. This feature allows the Tool to pass through the Sliding Sleeve that is not required to be shifted.

Product Code: 142

TECHNICAL DATA

NOMINAL SIZE	2"	2 1/2"	3"	3"
SLEEVE SIZE	1.875"	2.313"	2.750"	2.813"
ASSEMBLY NUMBER	142011118700	142011123100	142011127500	142011128100

ENGINEERING DATA:

KEYS EXPANDED – OD Min	1.94"	2.37"	2.84"	3.01"
LOCATOR DOG - MAX. OD	1.97"	2.40"	2.84"	2.90"
BODY OD	1.75"	2.18"	2.72"	2.72"
LENGTH	18.31"	18.94"	18.94"	18.94"
MATERIAL	Alloy	Alloy	Alloy	Alloy
PIN THREAD	15/16" - 10	15/16" - 10	1 1/16" - 10	1 1/16" - 10
FISHING NECK SIZE	1.375"	1.750"	2.313"	2.313"
BOTTOM THREAD CONNECTION	15/16" - 10	15/16" - 10	1 1/16" - 10	1 1/16" - 10
ACCESSORIES:	Assembly Sleeve (NS)	167151413200	167151413250	167151413300
	Test Sleeve (NS)	1671514187	1671514231	1671514275





SECTION V: SHIFTING TOOLS

Type 'ROTBP' Selective Positioning Tool Assembly:

TECHNICAL DATA

NOMINAL SIZE	4 1/2"	4 1/2"
SLEEVE SIZE	3.688"	3.813"
ASSEMBLY NUMBER	142011136800	142011138100

ENGINEERING DATA:

KEYS EXPANDED – OD Min	4.07"	4.08"
LOCATOR DOG - MAX. OD	3.78"	3.91"
BODY OD	3.62"	3.75"
LENGTH	19.88"	19.88"
MATERIAL	Alloy	Alloy
PIN THREAD	1 1/16" - 10	1 1/16" - 10
FISHING NECK SIZE	2.313"	2.313"
BOTTOM THREAD CONNECTION	1 1/16" - 10	1 1/16" - 10
ACCESSORIES:	Assembly Sleeve (NS)	167151413450
	Test Sleeve (NS)	1671514368
		1671514381

