

## **SECTION IV: PULLING TOOLS**

## Type 'ROTGRL' Pulling Tool Assembly: 2.00" – 4.00"

**Rebco** Types 'ROTGRL' Pulling Tool is a combination tool made up of the Type 'ROTGSL' Pulling Tool and Type 'ROTGU' Shear-Up Adapter.


TECHNICAL DATA						
NOMINAL SIZE	2"	2 1/2"	3″	4"		
ASSEMBLY NUMBER	4005130818700	4005130821800	4005130827500	4005130836804		
ENGINEERING DATA:						
MAXIMUM OD	1.81"	2.16"	2.72"	3.62"		
PIN THREAD CONNECTION	15/16" - 10	15/16" - 10	1 1/16" - 10	1 1/16" - 10		
FISHING NECK OD	1.375"	1.750"	2.313"	2.313"		
WILL ENGAGE FISHING NECK ID	1.38"	1.81"	2.31"	3.12"		
LENGTH	20.4"	20.9"	21.4"	22.7"		
MATERIAL	Alloy	Alloy	Alloy	Alloy		






## **SECTION IV: PULLING TOOLS**

Fig 2 - Comparative of 'ROTR\_' and 'ROTS\_' Pulling Tools







Series Type: 'ROTSB' and 'ROTSS'

## Chart: Pulling Tool Selection Guide

FISHING NECK	PULLING TOOL TYPE: SERIES			IAD TO DELEACE	
TYPE TO ENGAGE	SHEAR UP	SHEAR DOWN	SPECIAL	JAR TO RELEASE	
EXTERNAL	'ROTR_'		'RQ'	UP	
	'ROTJU_'				
	'ROTB_'				
		'ROTS_'	'SQ'	DOWN	
		'ROTJD_'			
		'RH'			
			'ROTSSJ'	DOWN w/Adapter	
			'RMF'	MODE: Up/Down	
INTERNAL	'ROTGR'			UP w/Adapter	
	'ROTGRL'				
		'ROTGS'		DOWN	
		'ROTGSL'			