

EXCEEDING EXPECTATIONS ONE TOOL AT A TIME

Gas Lift Kick Over Tools



PRODUCT DESCRIPTION: GAS LIFT - KICK OVER TOOLS

Gas Lift operations are efficient and cost efficient means of optimizing the production rates of the wells.

In this Section, *Rebco* presents the KOT's (Kick-Over Tools) offered. The Running and Pulling Tools, as well as some of the Accessories required, are listed in Sections, 3 and 4.

Chart: Kick-Over Tools available from Rebco




Table of Contents

GAS LIFT - KICK OVER TOOLS	PRODUCT CODE	PAGE
'ROTK' and 'ROTAK'	195	XI-1
'ROTL' and 'ROTL2-D'	194	XI-2-3
'ROTOK-5'	192	XI-4-5
'ROTOK-6'	192	XI-6
'ROTOM-1'	191	XI-7-8-9-10
'ROTOM-5'	191	XI-11
'ROTR'	193	XI-12



Type 'ROTL' Kick-Over Tool (KOT) Assembly: 2"- 2 1/2"

Rebco Type 'ROTL' KOT is used to install and retrieve 1" OD side pocket sub-surface control devices into Side Pocket Mandrels (SPM).

TECHNICAL DATA		
NOMINAL SIZE	2" - 2 1/2"	
ASSEMBLY NUMBER	194082250	
KICK OVER TOOL TYPE Type 'ROTL'		
ENGINEERING DATA:		
ENGINEERING I	DATA:	
PIN THREAD CONNECTION	DATA: 15/16" – 10	
PIN THREAD CONNECTION	15/16" – 10	




'ROTL' Series KOT



Type 'ROTL-2D' Kick-Over Tool (KOT) Assembly: 2"-2 1/2", 3"

Rebco Type 'ROTL-2D' KOT is used to install and retrieve 1" and 1 1/2" OD Sub-surface control devices into Side Pocket Mandrels (SPM).

TECHNICAL DATA			
NOMINAL SIZE	2" - 2 1/2"	3"	
ASSEMBLY NUMBER	194082032250	194082033000	
KICK OVER TOOL TYPE	Type 'ROTL-2D'	Type 'ROTL-2D'	
ENGINEERING DATA:			
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	
FISHING NECK OD	1.187"	1.187"	
LENGTH	21"	21″	



'ROTL-2D' Series KOT



Type 'ROTOK-5' Kick-Over Tool (KOT) Assembly: 2" – 4 1/2"

Rebco Type 'ROTK-5' KOT is used to install and retrieve 1" OD side pocket sub-surface control devices in to Side Pocket Mandrels (SPM).


Type 'ROTOK-5'Kick-Over Tools have spring type centralizers.

Product Code: 192

NOMINAL SIZE	2"	2 1/2"	
ASSEMBLY NUMBER	192202452000	192202452500	
ENGINEERING DATA:			
MAXIMUM OD	1.750″	2.063"	
Tubing ID required for proper tool orientation	1.945"	2.437"	
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	
FISHING NECK OD	1.375"	1.375"	
LENGTH	64 7/8"	67.0"	
MATERIAL	Alloy	Alloy	

ACCESSORY:

Service Tool: Type ST for Detent Spring 5514151	Service Tool: Type 'ST' for Detent Spring	5514151
---	---	---------



Type 'ROTOK-5' KOT

Page XI-4




Type 'ROTOK-5' Kick-Over Tool (KOT) Assembly:

TECHNICAL DATA			
NOMINAL SIZE	3"	4 1/2"	
ASSEMBLY NUMBER	192202453000	192202454500	
ENGINEERING DATA:			
MAXIMUM OD	2.500"	3.500"	
Tubing ID required for proper tool orientation	2.921"	3.958"	
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	
FISHING NECK OD	1.375"	1.375"	
LENGTH	71 1/8"	71 7/8"	
MATERIAL	Alloy	Alloy	

ACCESSORY:

Service Tool: Type 'ST' for Detent Spring	5514151
Service 1001, Type ST 101 Detelli Sprilla	3314131



Type 'ROTOK-5' KOT

Page XI-5

Rebco Oil Tools, Inc. Calgary, Alberta, Canada



Type 'ROTOK-6' Kick-Over Tool (KOT) Assembly: 2 1/2" - 4 1/2"

Rebco Type 'ROTOK-6' KOT is used to install and retrieve 1" OD side pocket sub-surface control devices in to Side Pocket Mandrels (SPM).

Type 'ROTOK-6' Kick-Over Tools have sleeve type centralizer.

Product Code: 192

TECHNICAL DATA			
NOMINAL SIZE	2 7/8"	3"	4 1/2"
ASSEMBLY NUMBER	192202462500	192202463000	192202464500
ENGINEERING DATA:			
MAXIMUM OD	2.223"	2.500"	3.500"
Tubing ID required for proper tool orientation	2.437"	2.921"	3.958"
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	15/16" – 10
FISHING NECK OD	1.375"	1.375"	1.375″
LENGTH	67.0"	71.125"	71.87"
MATERIAL	Alloy	Alloy	Alloy
ACCESSODY.			

ACCESSORY:

Service Tool: Type 'ST' for Detent Spring	5514151

4 1/2"

'ROTOK-6' Series KOT

Page XI-6



Type 'ROTOM-1' Kick-Over Tool (KOT) Assembly: 2" - 7"

Rebco Type 'ROTOM-1' KOT is used to install and retrieve 1 1/2" OD side pocket sub-surface control devices into Side Pocket Mandrels (SPM).

NOTE: Type 'ROTOM-1' Kick-Over Tools are available (Variation) with or without Catcher Sub-Assembly, when ordering, please specify.

Product Code: 191

TECHNICAL DATA			
NOMINAL SIZE	2"	2 1/2"	3"
ASSEMBLY NUMBER	191200912000	191200912500	191200913000
ENGINEERING DATA:			
VARIATION Available, See Note			YES Note
MAXIMUM OD	1.859"	2.223"	2.739"
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	15/16" – 10
FISHING NECK OD	1.375″	1.375"	1.375"
LENGTH	88.687"	81.750"	81.875"
MATERIAL	Alloy	Alloy	Alloy
ACCESSORY:		•	
SPACER BAR - (1 1/2" x 11 1/4")	5500819	5500819	5500819

NOTE: All *Rebco* KOTs with Catcher:

2 1/2" "ROTOM-1" catchers 00 QTY 2 2 1/2" "ROTOM-1" catchers 00 QTY 2



Type 'ROTOM-1' Kick-Over Tool (KOT) Assembly:

TECHNICAL DATA		
NOMINAL SIZE	4"	
ASSEMBLY NUMBER	191200914500	
ENGINEERING DATA:		
MAXIMUM OD	3.723"	
PIN THREAD CONNECTION	15/16" – 10	
FISHING NECK OD	1.375"	
LENGTH	81.75""	
MATERIAL	Alloy	
ACCESSORY:		
SPACER BAR - (1 1/2" x 11 1/4")	5500819	





Type 'ROTOM-1' Kick-Over Tool (KOT) Assembly:

TECHNICAL DATA			
NOMINAL SIZE	5″	5" <u>NOTE</u>	
ASSEMBLY NUMBER	191200915000	191200915001	
ENGINEERING DATA:			
MAXIMUM OD	4.068"	3.920"	
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	
FISHING NECK OD	1.375"	1.375"	
LENGTH	82.187"	82.187"	
MATERIAL	Alloy	Alloy	
ACCESSORY:			
SPACER BAR - (1 1/2" x 11 1/4")	5500819	5500819	

Note: Assembly No 191200915001 is Special OD to pass through 4.125" SSSV





Type 'ROTOM-1' Kick-Over Tool (KOT) Assembly:

TECHNICAL DATA				
NOMINAL SIZE	5 1/2"			
ASSEMBLY NUMBER	191200915500			
ENGINEERING DATA:				
MAXIMUM OD	4.250"			
PIN THREAD CONNECTION	1 9/16" – 10			
FISHING NECK OD	2.313"			
LENGTH	78.125"			
MATERIAL	Alloy			
ACCESSORY:				
SPACER BAR - (1 1/2" x 11 1/4")	5500819			






Type 'ROTOM-5' Kick-Over Tool (KOT) Assembly: 3 1/2"

Rebco Type 'ROTOM-5' KOT is used to install and retrieve 1 1/2" OD side pocket sub-surface control devices into Side Pocket Mandrels (SPM).

Type 'ROTOM-5' KOT uses a ball detent and detent spring design to ease redress procedure in the field.

TECHNICAL DATA					
NOMINAL SIZE	2 1/2"	3 1/2"			
ASSEMBLY NUMBER	191200952500	191200953500			
ENGINEERING DATA:					
MAXIMUM OD (Centralizing Retracted)	2.250"	2.531"			
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10			
FISHING NECK OD	1.375″	1.375"			
LENGTH	93.812"	93.812"			
MATERIAL	Alloy	Alloy			
ACCESSORY:					
SPACER BAR - (1 1/2" x 11 1/4")	5500819	5500819			





Type 'ROTR' Kick-Over Tool (KOT) Assembly: 2" - 2 1/2" and 3 1/2"

Rebco Type 'ROTR' KOT is used to install and retrieve 1 1/2" OD side pocket subsurface control devices into Side Pocket Mandrels (SPM).

TECHNICAL DATA				
NOMINAL SIZE	2"	2 1/2"	3 1/2"	
ASSEMBLY NUMBER	19313202000	19313202500	19313203000	
ENGINEERING DATA:				
MAXIMUM OD - Arms Retracted	1.859"	2.281"	2.500"	
MAXIMUM OD - Arms Open	3.813"	3.813"	5.688"	
PIN THREAD CONNECTION	15/16" – 10	15/16" – 10	15/16" – 10	
BOX THREAD CONNECTION	15/16" – 10	15/16" – 10	15/16" – 10	
LENGTH	27 1/8"	27 1/8"	30 1/2"	
MATERIAL	Alloy	Alloy	Alloy	

