

SECTION XVI: PLUG ASSEMBLIES for NIPPLES & TUBING

Type 'ROTFWG-1' Plug Choke with Removable Mandrel (TOP No-Go): 4 1/2"

NOTE: Type 'ROTFWG-1' Plug Choke (By-pass Blanking Plug) with Removable Mandrel uses different type of Lock (Dog).

Plug Chokes are available in a variety of Materials, suitable for down-hole conditions.

Product Code: 21

TECHNICAL DATA					
NOMINAL SIZE			4 1/2"		
SEAL BORE SIZE			3.688"	3.750"	3.813"
ASSEMBLY NUMBER			2125170513680	2125170513750	2125170513810
ENGINEERING DATA:					
MAXIMUM OD - (No-Go)			3.740"	3.802"	3.864"
FISHING NECK OD			3.125"	3.125"	3.125"
RUNNING TOOL Note *1	4 1/2" 'ROTC-1'		41022014500	41022014500	41022014500
	4 1/2" 'ROTBG'		4101054500	4101054500	4101054500
PULLING TOOL Note *2	SHEAR DOWN	'ROTSB'	4014014000	4014014000	4014014000
		'ROTJDC' (a) (b)	400703024000 (a)	400703024000 (b)	400703024000
	SHEAR UP	'ROTRB'	4013014000	4013014000	4013014000
		'ROTJUC' (a) (b)	400716024000 (a)	400716024000(b)	400716024000
PULLING PROBE 4 1/2" Type 'ROTB'		1950185300	1950185300	1950185300	
LENGTH			20.3"	20.3"	20.3"
MATERIAL			Alloy	Alloy	Alloy



Reference: REDRESS KIT - Parts of (DET 8), Only 'V' Packing (Qty - 6 only) included as part of the REDRESS KIT

Note: *1 – either / or Running Tools can be Used

Note: *2 CAUTION:

- (a) Pulling Tool 'ROTJDC' and 'ROTJUC' will not pass thru 3.688" Seal Bore.
- (b) Pulling Tool 'ROTJDC' and 'ROTJUC' will not pass thru 3.750" Seal Bore, but may be used for retrieving if there is no restriction in the tubing above the accessory smaller than the next larger Seal Bore.
- See PRODUCT CODE 10, Lock Mandrels: Type 'S-1,2', 'W-1,2' and 'Z-1,2' for more details