



SECTION XV: EQUALIZING SUB-ASSEMBLIES and ACCESSORIES

Type 'ROTPX' Equalizing Prong and Valve Sub-Assembly: 1.500" – 4.562"

Rebco Type 'ROTPX' Equalizing Prong and Valve Sub-Assembly, when attached to Type 'ROTX' and/or 'ROTXN' Lock Mandrel Assembly, converts the Lock Mandrel to a Plug Choke, with equalizing device, capable of holding pressure differentials from above or below.

Product Code: 24

TECHNICAL DATA				
NIPPLE SEAL BORE	1.500"	1.625"	1.875"	2.313"
SUB-ASSEMBLY NUMBER	24111815031	24111816231	24111818731	24111823131
ENGINEERING DATA:				
MAXIMUM OD (NO-GO)	1.495"	1.620"	1.870"	2.307"
BOX THREAD CONNECTION	1 1/8" - 16	1 1/8" - 16	1 3/8" - 14	1 3/4" - 12
PRONG FISHING NECK SIZE	1.000"	1.000"	1.375"	1.375"
PRONG LENGTH	26.0"	26.0"	23.38"	23.46"
LENGTH	29.87"	29.87"	26.46"	26.56"
'V' PACKING OD	.630"	.630"	.938"	1.250"
PRONG RUNNING / PULLING TOOL	400703021375	400703021375	4014012000	4014012000
MATERIAL *	Norm Alloy	Norm Alloy	Norm Alloy	Norm Alloy

* Norm Alloy is suitable for H2S Service (NACE MR-01-75, Latest Revision)

TECHNICAL DATA				
NIPPLE SEAL BORE	2.750"	2.813"	2.875"	3.313"
SUB-ASSEMBLY NUMBER	24111827530	24111828130	24111828730	24111833130
ENGINEERING DATA:				
MAXIMUM OD (NO-GO)	2.745"	2.808"	2.870"	3.307"
BOX THREAD CONNECTION	2 1/4" – 12 SLB	2 1/4" – 12 SLB	2 1/4" – 12 SLB	2 3/4" – 12 SLB
PRONG FISHING NECK SIZE	1.375"	1.375"	1.375"	1.375"
PRONG LENGTH	25.18"	25.18"	25.18"	25.18"
LENGTH	28.13"	28.13"	28.13"	28.13"
'V' PACKING OD	1.500"	1.500"	1.500"	1.500"
PRONG RUNNING / PULLING TOOL	4014012000	4014012000	4014012000	4014012000
MATERIAL *	Norm Alloy *	Norm Alloy *	Norm Alloy *	Norm Alloy *

* Norm Alloy is suitable for H2S Service (NACE MR-01-75, Latest Revision)





SECTION XV: EQUALIZING SUB-ASSEMBLIES and ACCESSORIES

Type '**ROTPX**' Equalizing Prong and Valve Sub-Assembly:

TECHNICAL DATA				
NIPPLE SEAL BORE	3.688"	3.813"	4.313"	4.562"
SUB-ASSEMBLY NUMBER	24111836830	24111838130	24111843130	24111845630
ENGINEERING DATA:				
MAXIMUM OD (NO-GO)	3.682"	3.807"	4.307"	4.556"
BOX THREAD CONNECTION	3 1/16" – 12 SLB	3 1/16" – 12 SLB	3 1/4" – 12 SLB	3 3/4" – 12 SLB
PRONG FISHING NECK SIZE	2.313"	2.313"	3.125"	3.125"
PRONG LENGTH	34.84"	34.84"	39.04"	39.04"
LENGTH	37.15"	36.95"	41.2"	41.23"
'V' PACKING OD	1.500"	1.500"	2.313"	2.313"
PRONG RUNNING / PULLING TOOL	4014013000	4014013000	4014014000	4014014000
MATERIAL *	Norm Alloy *	Norm Alloy *	Norm Alloy *	Norm Alloy *

* Norm Alloy is suitable for H2S Service (NACE MR-01-75, Latest Revision)

Equalizing Sub-Assemblies are available in variety of Materials to suit Well Conditions.

