



SECTION I: TOOL STRING

Type '**HD**' Heavy Duty Rope Socket Assembly – '**QLS**' Connection: 1 1/2" – 2 1/2"

Rebco Type '**HD**' Heavy Duty Rope Socket is designed for Heavy Duty Wireline Work.

Type '**HD**' Rope Socket is made up of Type '**HO**' Rope Socket Assembly with an '**RQLD**' Bottom Sub-Assembly.

The wire should be passed through the body and the clamp Sub-Assembly. The unique design will trap the wire; held in place by socket screws.

Alloy Material is used to manufacture Rebco Rope Sockets. Materials suitable for specific well conditions are available.

Must be ordered by Wire Size in use.

TECHNICAL DATA

NOMINAL SIZE	1 1/2"	1 3/4"	1 7/8"	2 1/8"	2 1/2"
ASSEMBLY NUMBER	10006031500_	10006031750_	10006031870_	10006032120_	10006032500_

ENGINEERING DATA:

MAXIMUM OD	1.50"	1.75"	1.88"	2.12"	2.50"
FISHING NECK OD	1.375"	1.750"	1.750"	1.750"	2.313"
LENGTH	17.45"	19.1"	19.1"	19.1"	19.1"
BOTTOM CONNECTION	'RQLD'	'RQLD'	'RQLD'	'RQLD'	'RQLD'
MATERIAL	Alloy	Alloy	Alloy	Alloy	Alloy

