



SECTION III: RUNNING TOOLS

Type 'ROTP' Running Tool Assembly: 1 3/16" – 3"

The **Rebco 'ROTP'** Running Tool is specifically designed for use with sub-surface devices featuring removable prong assemblies. Its extended internal recess accommodates the prong fishing neck, which projects above the main tool fishing neck, ensuring proper alignment and secure running of the device into the wellbore.

* Running Neck ID is determined by the Type of Sub-Surface Tool used. If '**ROTP**' Running Tool listed in the box is not suitable, please Specify Fishing Neck Size or Tool Type when ordering.

Type '**ROTP**' Running Tool can be ordered with Prong Box Thread; please specify.



TECHNICAL DATA							
NOMINAL SIZE	ASSEMBLY PART NUMBER	ENGINEERING DATA					
		LENGTH	THREAD CONNECTION		FISHING NECK OD	MAX OD	RUNNING NECK ID *
			PIN	PRONG			
1 3/16"	41113	6.19"	5/8" - 11	None	1.000"	1.31"	.413"
1 1/2"	41117	6.00"	15/16" - 10	None	1.187"	1.42"	1.010"
2"	41111	8.00"		None	1.375"	1.69"	1.163"
2 1/2"	41112	7.50"		None	1.750"	2.00"	1.574"
3"	41116	5.12"	1 1/16" - 10	None	2.313"	2.50"	1.950"