



SECTION XIII: LANDING NIPPLES

TYPE 'BR' LANDING NIPPLE: Part No. 110113_____

Rebco Type 'BR' Landing Nipple is a Bottom No-Go Nipple.
The profile machined in the Nipple accepts Bottom No-Go Locks.

AVAILABILITY CHART:

TECHNICAL DATA								
Tubing OD		NIPPLE						
		Seal Bore		Size	No-Go ID		Min OD	
Inches	mm	Inches	mm		Inches	mm	Inches	mm
1.660	42.16	1.187	30.15	1.18	1.135	28.83	1.875	47.63
1.900	48.26	1.437	36.50	1.43	1.385	35.18	2.109	53.57
		1.500	38.10	1.50	1.447	36.75		
2 1/16	52.37	1.562	39.67	1.56	1.510	38.35	2.250	57.15
2 3/8	60.33	1.781	45.24	1.78	1.728	43.89	2.560	65.02
		1.812	46.02	1.81	1.760	44.70		
		1.875	47.63	1.87	1.822	46.28		
2 7/8	73.02	2.062	52.37	2.06	1.978	50.24	3.109	78.97
		2.125	53.97	2.12	2.035	51.68		
		2.250	57.15	2.25	2.197	55.68		
		2.312	58.72	2.31	2.259	57.37		
3 1/2	88.9	2.562	65.07	2.56	2.442	62.03	3.687	93.65
		2.750	69.85	2.75	2.697	68.50		
		2.812	71.42	2.81	2.758	70.07		
4	101.60	3.125	79.38	3.12	3.072	78.03	Coupling OD	
		3.312	84.12	3.31	3.242	82.35		
4 1/2	114.30	3.688	93.68	3.68	3.625	92.08		
		3.750	95.25	3.75	3.700	93.98		
5	127.0	3.812	96.82	3.81	3.759	95.48		
		4.000	101.60	4.00	3.910	99.31		
		4.125	104.78	4.12	4.035	102.49		
5 1/2	139.70	4.312	109.52	4.31	4.223	107.26		
		4.562	115.87	4.56	4.472	113.59		
6 5/8	168.28	4.750	120.65	4.75	4.660	118.36		
		5.250	133.35	5.25	5.150	130.81		
7	177.80	5.500	139.70	5.50	5.400	137.16		
		5.750	146.05	5.75	5.625	142.88		
7 5/8	193.68	5.953	151.21	5.95	5.828	148.03		
		6.125	155.58	6.12	6.000	152.40		
		6.375	161.92	6.37	6.257	158.93		



Type 'BR'

Min OD – Machined to the Tubing Joint OD or Coupling OD