



SECTION II: SERVICE TOOLS

Type 'AO' Tubing End Locator Assembly: 1/2" – 5 1/2"

Rebco Type 'AO' Tubing End Locator is used to locate the lower end of the tubing so that its depth may be measured accurately.

The tool features a slotted body housing a spring-loaded finger, which is held in place by a shear pin. As the tool exits the lower end of the tubing, the finger extends to a perpendicular position, indicating the tubing has ended. The finger will not re-enter the tubing until the shear pin is released, ensuring a clear and reliable depth reference.

Product Code: 163

TECHNICAL DATA

NOMINAL SIZE	1/2"	3/4"	7/8"	1"
ASSEMBLY NUMBER	16300204	16300208	16300201	16300202

ENGINEERING DATA:

MAXIMUM OD	.50"	.75"	.88"	1.00"
PIN THREAD CONNECTION	3/8" - 16	1/2" - 13	5/8" - 11	5/8" - 11
FISHING NECK OD	None	.687"	.75"	.75"
BOTTOM THREAD CONNECTION	None	None	None	None
EXTENDED DIAMETER with FINGER	.95"	1.50"	1.94"	2.02"
LENGTH	8.0"	8.50"	8.50"	8.50"
MATERIAL	Alloy	Alloy	Alloy	Alloy



TECHNICAL DATA

NOMINAL SIZE	2" - 2 1/2"	3" - 3 1/2"	4 1/2"	5 1/2" - 7"
ASSEMBLY NUMBER	16300203	163002011	163002012	163002013

ENGINEERING DATA:

MAXIMUM OD	1.70"	2.00"	3.00"	3.46"
PIN THREAD CONNECTION	15/16" - 10	15/16" - 10	1 1/16" - 10	1 1/16" - 10
FISHING NECK OD	1.375"	1.375"	1.750"	2.313"
BOTTOM THREAD CONNECTION	1.375"	1.375"	1 1/16" - 10	1 1/16" - 10
EXTENDED DIAMETER with FINGER	3.05"	4.07"	4.59"	5.06"
LENGTH	11.5"	11"	11"	11"
MATERIAL	Alloy	Alloy	Alloy	Alloy



NOTE: Sampler Tube with Ball or Flapper bottom available - Specify OD and Length when ordering.