



SECTION II: SERVICE TOOLS

Anchor Type Stops Assemblies for Tubing Perforator: 2 3/8" – 4 1/2"

Rebco Type '**CS**' and/or Type '**TS**' Anchor Stops are designed to screw directly into the base of the Tubing Perforator, and as a unit, to be set at desired depth.

Product Code: 62

Type '**CS**' Collar Stop Anchor Assemblies:

Rebco Type '**CS**' Collar Stop Anchor is used in the Tubing as a Stop; screwed directly to the bottom of the Tubing Perforator, to be set and pulled as a unit.

TECHNICAL DATA				
NOMINAL SIZE	2" (2 3/8")	2 1/2" (2 7/8")	3 1/2"	4 1/2"
ASSEMBLY NUMBER	6202142000	6202142500	6202143500	6202144500
ENGINEERING DATA:				
MAXIMUM OD	1.75"	2.19"	2.75"	3.75"
PIN THREAD CONNECTION	15/16" - 10	1 1/16" - 10	1 1/16" - 10	1 1/16" - 10
FISHING NECK OD	1.375"	1.750"	2.313"	2.313"
LENGTH	10.72"	11.31"	11.81"	11.61"
MATERIAL	Alloy	Alloy	Alloy	Alloy

Special Collet OD for 3 1/2" Collar Stop Anchor that will pass through 2.750" Nipple is available.

Product Code: 62

Type '**TS**' Slip Stop Anchor Assemblies:

Rebco Type '**TS**' Slip Stop Anchor is used in the Tubing as a Stop; screwed directly to the bottom of the Tubing Perforator, to be set and pulled as a unit.

TECHNICAL DATA				
NOMINAL SIZE	2" (2 3/8")	2 1/2" (2 7/8")	3 1/2"	4 1/2"
ASSEMBLY NUMBER	6215142000	6215142500	6215143500	6215144500
ENGINEERING DATA:				
MAXIMUM OD - SET IN PLACE	1.998"	2.492"	3.05"	3.75"
PIN THREAD CONNECTION	15/16" - 10	1 1/16" - 10	1 1/16" - 10	1 1/16" - 10
FISHING NECK OD	1.375"	1.750"	2.313"	2.313"
LENGTH - SET IN PLACE	14.25"	14.15"	16.05"	17.8"
MATERIAL	Alloy	Alloy	Alloy	Alloy

